

# FICHA TECNICA

|                   |                             |
|-------------------|-----------------------------|
| Familia           | TUERCAS                     |
| Producto          | 0744                        |
| Descripción       | DIN 985 C10                 |
| Mortaja           |                             |
| Calidad           |                             |
| Material          |                             |
| Acabados estándar | CINCADO $\geq 3\mu\text{m}$ |



## APLICACIONES

Tuerca de freno con inserto de plástico de alta resistencia.

## MEDIDAS

| d        | M3  | M4  | M5  | M6 | M7   | M8   | M10  | M12  | M14  | M16  |
|----------|-----|-----|-----|----|------|------|------|------|------|------|
| m (mín.) | 2,4 | 2,9 | 3,2 | 4  | 4,7  | 5,5  | 6,5  | 8    | 9,5  | 10,5 |
| S        | 5,5 | 7   | 8   | 10 | 11   | 13   | 17   | 19   | 22   | 24   |
| e1       | 6   | 7,7 | 8,9 | 11 | 12,1 | 14,4 | 18,9 | 21,1 | 24,5 | 26,7 |
| h        | 4   | 5   | 5   | 6  | 7,5  | 8    | 10   | 12   | 14   | 16   |

| d        | M18  | M20  | M22  | M24  | M30  |
|----------|------|------|------|------|------|
| m (mín.) | 13   | 14   | 15   | 15   | 19   |
| S        | 27   | 30   | 32   | 36   | 46   |
| e1       | 30,1 | 33,5 | 35,7 | 39,9 | 51,3 |
| h        | 18,5 | 20   | 22   | 24   | 30   |

